

# Evidence of Performance

Ageing behaviour of insulating glass units according to  
DIN EN 1279-2



## Test Report

no. 14-000702-PR01  
(PB-H01-09-en-01)

Client **Pellini S.p.A.**  
Via Fusari, 19  
26845 Codogno-Lo  
Italy

### Basis

DIN EN 1279-2 : 2003-06;  
Glass in building - Insulating  
glass units - Part 2: Long term  
test method and requirements  
for moisture penetration

Product	Insulating glass units - gas filled
Designation	Sanco Silverstar EN2plus 2-fach
Exterior dimensions (W x H) in mm	350 x 500
Construction in mm	4 / 27 / 4
Spacers	Aluminium spacer, company Pellini
Sealants	
External	Basis Polysulfide, GD 116, company Kömmerling
Internal	Basis Polyisobutylene, GD 115, company Kömmerling
Special features	Corner key with motor connectors

### Instructions for use

This test report serves to demonstrate the moisture penetration of insulating glass units.

It serves as a basis (ITT) for CE-marking according to EN 1279-5.

### Validity

The data and results given relate solely to the tested and described specimen.

The long term test does not imply any statement on characteristics regarding performance and quality.

The insulating glass unit fulfils the requirements of



DIN EN 1279-2

ift Rosenheim  
27.08.2014

Irina Hausstetter, Dipl.-Ing. (FH) Technische  
Chemie  
Head of Testing Department  
Material Testing

Miriam Kaube, B.Eng.  
Operating Testing Officer  
Material Testing

### Notes on publication

The Ift-Guidance Sheet "Conditions and Guidance for the Use of Ift Test Documents" applies.

The cover sheet can be used as abstract.

### Contents

The report contains a total of 7 pages

- 1 Object
- 2 Procedure
- 3 Detailed results
- 4 Evaluation
- 5 Summary